

Loaders | Unloaders

8042TDF (Direct Feed)



Performance Specification

Operating Rate	Stockpile Height	Stockpile Capacity	Conveyor Width	Conveyor Length
600+ TPH*	11.330m (37)	2162 m ³ *	1050mm (42")	23,500mm (77)

* Depending on material density and set-up

Dimension Specification

Transport Dimensions			Working Dimensions		
Height	Width	Length	Width	Length	Weight (Est.)
2590mm (8' 5")	2250mm (7' 4")	12,000mm (39' 4")	2250mm (7' 4")	21,170mm (69' 5")	15,000kgs (33,069 lbs)

8042TDF (Direct Feed)

The Trackstack 8042TDF (Direct Feed) machine has all the features of a standard 8042T but also has the added benefit of having a large feed hopper. This allows it to be fed direct by a Wheeled Loader or Excavator and with its Hi-Torque, fuel efficient drive system it has more than enough power.

With fold down hopper sides the feed height of this machine can be easily changed. This also allows it to receive material directly from a crusher or screen or be installed in a close circuit application.

The 8042TDF integrates easily into the Tesab range of crushers and screeners making it the ideal solution in any situation.



Features & Benefits

- Large direct feed hopper allowing up to 600+ tonnes per hour production rate
- Unique 'Boomerang' system allows a stockpile capacity of 2162 m³ (3460 Tonnes @1.6T/m³)
- Hi-Torque drive and engine size combine to reduce fuel consumption
- Range of optional extras available
(Contact your local Trackstack representative for details)

Trackstack 
Reaching New Heights